

拖輪訂貨說明

PULLER Order Guide

PL P 5515 BROTHER LT2 B842-401

1 ●機型代號說明
● Puller Model Table

4 ●按裝之針車廠牌機型
● Adaptable Sewing Machine Brand and Model

5 ●自動切線及附屬配件編號
● Auto Thread Trimmer or Other Attachment Device No.

機型 MODEL	適用針車 ADAPTABLE MACHINE	說明 DESCRIPTION
PS	單針、雙針 Single or Twin Needle	輪徑25mm，輪子與車針距離僅28-30mm，適用於薄布料短距離車縫 Diameter 25mm Roller, 28-30mm Between Needle and Roller. For Short Thin Material, Curve and Short Sewing.
PL	單針、雙針 Single, Twin or Multiple Needle	輪徑55mm，輪子與車針距離50mm以上，適用於一般厚、薄布料 Diameter 55mm Roller, More than 50mm Between Needle and Roller. For General Material.
PL-S1	前縫車 Flat Bed Coverstitch	專用基座，輪徑55mm，輪子與車針距離50mm以上，適用於一般厚、薄布料 Special Bracket, Diameter 55mm Roller, More than 50mm Between Needle and Roller. For General Material.
PL-S2	筒形前縫車 Cylinder Bed Coverstitch	專用基座，附下輪，輪徑55mm，輪子與車針距離50mm以上，適用於一般厚、薄布料 Special Bracket, Lower Roller and Diameter 55mm Roller, More than 50mm Between Needle and Roller. For General Material.
PT	單針、雙針 Single or Twin Needle	上下輪驅動拉力特強，輪徑55mm，輪子與車針距離130mm以上，適用於薄到極厚物、長距離中縫 Powerful Upper and Lower Roller, Diameter 55mm Roller, More than 130mm Between Needle and Roller. For General Material.
PT-H		極厚物專用 Same As PT, For Heavy Material.
PT-L		長臂型 Same As PT, For Long Arm.
PF	原車專用 Feed-Off-Arm	輪徑55mm，輪子與車針距離50mm以上，為一般布料用 Diameter 55mm Roller, More than 50mm Between Needle and Roller. For General Material.
PF-H		為厚物專用，功能同PF Same As PF, For Heavy material.
PY	單針、雙針 Single Needle or Twin Needle	固定於車板，功能同PT Fix on Table, Same As PT Puller.
PY-C	前縫車 Coverstitch	固定於車板，功能同PT Fix on Table, Same As PT Puller.
PY-SP	前拉式單針車 Single Needle, Front Pull	義大利麵專用，固定於車板 Special for Spaghetti Sewing, Fix on Table.
PW	手背可動型盲縫車用 Blind Stitch With Moveable Arm	皮帶式下送料，適用於潛水衣布料 Drive Belt Feed, For Diving Suit Material.
PW-L		長臂型用 Same As PW, For Long Arm.
PG	包縫車用 Overlock	小輪輪徑28mm，適用於薄物布料 Diameter 28mm Roller, For Thin Material.
PR	包縫車用 Overlock	齒形皮帶接頭，適用於薄物布料 Feeding By Timing Belt, For Thin Material.
PO	包縫車用 Overlock	齒形皮帶接頭，適用於各種輪織多層、膠邊及易滑布料 Feeding By Timing Belt, For Multi-Layer Tough Abrasive and Silky Material.
PO-F	包縫車用 Overlock	POLQ領專用，附包邊器，膝部氣動開關及左右活動導布器 Special for Knit Shirt Collars, With Knee Pneumatic Switch to Act the Moveable Folder Right or Left Side.
PK	包縫車用 Overlock	上下輪驅動拉力特強，輪徑55mm，輪子與車針距離200mm以上，適用於薄到極厚物長距離中縫 Powerful Upper and Lower Roller, Diameter 55mm Roller, More than 200mm Between Needle and Roller. For Thin to Very Thick Material.
PK-SP	前拉式包縫車專用 Overlock, Front Pull	義大利麵專用 Special for Spaghetti Sewing

2 ●輪子材質與外型
● Roller Material & Figures

代號 Code	P	S	T	C
材質 Material	PU 平面 Polyurethane Plain	鋼齒面 Steel Teeth	塑膠齒面 Plastic Teeth	塑膠平面 Plastic Plain
外型 Figure				
			PS、PG 不適用 Not for PS、PG	

※PW、PR、PO 帶式規格不適用
※ Not For PW、PR、PO Series With Belt Driven Type

3 ●輪子規格
● Roller Sizes

	單位: mm Unit: mm	
	D 直徑 Diameter	W 寬度 Width
上輪 Upper roller	55	15, 35, 50
	25	10, 15 (PS 專用) (PS only)
下輪 Lower roller	25	60 (PK 專用) (PK only)
	25	80 (PT, PY 專用) (PT, PY only)
	30	22 (PF 專用) (PF only)

※PW、PR、PO 帶式規格不適用
※ Not For PW、PR、PO Series With Belt Driven Type

拖輪規格表

PULLER Specification List

機型 Model	PS PS-B	PL PL-B	PL-S1	PL-S2	PT PT-H PT-L	PY PY-C PY-SP	PF PF-H	PW PW-L	PG	PR	PO PO-F	PK PK-SP
功能 Function												
驅動方式 Driven Way	上輪 Upper Roller	上輪 Upper Roller	上輪 Upper Roller	上輪 Upper Roller	上下輪 Upper & Lower Roller	上下輪 Upper & Lower Roller	上輪 Upper Roller	下皮帶 Lower Belt	上輪 Upper Roller	換皮帶 Belt Belt	上皮帶 Upper Belt	上下輪 Upper & Lower Roller
變速機規格(變速) Transmission Type (intermittent)	P-2	PL-P-2 PL-B-P-2	P-2	P-2	PT-P-2 PT-H-P-1 PT-L-P-1	P-2	PF-P-2 PF-H-P-1	P-1	P-2	P-2	P-1	P-2
拉布輪與針距離(最小)mm The distance Between the Roller and Needle (MIN.) mm	28	50	65	65	130	150	60		40	40		200
拉布輪規格(標準配件) Roller Type (Regular)	P2510	P5515	P5550	T5550 T2560	P5550 P2580	P5550K P2580K	P5515 P3022	180X1.037	P2811	335LX1.08	475DX1.10	P5535K P2560K
拉引長度(mm) Puller Length (mm)	0.3-6	0.3-6	0.3-6	0.3-6	0.3-8	0.3-6	PF:0.3-6 PF-H:0.3-8	0.3-6	0.3-6	0.3-6	0.3-6	0.3-6
最高縫速(連續車縫/間歇車縫) Sewing MAX. Speed (Continuous / Intermittent)	4000/6000				PT:4000/6000 PT-H:3000/4000 PT-L:3000/4000	4000/6000	PF:4000/6000 PF-H:3000/4000	3000/4000	4000/6000			
電源 Power	AC 100-240V 自動切換 AC 100-240V AUTO SWITCHING											

※拖輪系列產品說明
※ PULLER SERIES - PRODUCT SPEC.